



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
© COPYRIGHT - By - TE CONNECTIVITY ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN APVD
HB	-		E	REMOVED THE RIB ON THE BASE TO CASE ECO-15-011310	08-Dec-15	YS.H HLC
			E1	ADD NEW PN ECO-17-004477	17-Jan-18	WQ.Y K.T



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN H.Sasaki		 TE Connectivity			
		CHK Y.Oikawa					
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD A.Nagai		NAME	
		0 PLC ± -		PRODUCT SPEC		-	
		1 PLC ± -		-		OJ-SH-LMH SPEC	
		2 PLC ± -		APPLICATION SPEC		-	
		3 PLC ± -		-		SIZE	
		4 PLC ± -		-		CAGE CODE	
		ANGLES ± -				DRAWING NO	
MATERIAL		FINISH		WEIGHT		RESTRICTED TO	
-		-		-		A300779 C- 1461247	
CUSTOMER DRAWING				SCALE 5:1		SHEET 1 of 2	
						REV E1	

LOC	DIST	REVISIONS				
HB	-	P	LTR	DESCRIPTION	DATE	DWN
		-	-	SEE SHEET 1	-	-



NOTES:

1.LOT NO. SYSTEM AS FOLLOWING:

0 5 4 7
WEEK
YEAR

4.ADD LOT NO. SYSTEM AS FOLLOWING;

1 1 A
I II III

I, DIGITS FOR DAY OF THE WEEK

- 1...MONDAY IN THIS WEEK;
- 2...TUESDAY IN THIS WEEK;
-
- 7...SUNDAY IN THIS WEEK

II, DIGITS FOR SHIFT OF THE DAY

- 1...DAY SHIFT IN THIS DAY;
- 2...NIGHT SHIFT IN THIS DAY;

III, ONE CHARACTER DISTINGUISH THE LINE IDENTITY, SUCH AS: A,B,.....Z

2.TERMINAL DIMENSION IS BEFORE SOLDER DIP;

3.FOR THE TIN-PLATING OF THE PINS:

+0.1mm FOR WIDTH,THICKNESS AND DIAMETER.
+0.5mm FOR LENGTH.

(E)	A	1461247-7	OJ-SH-112LMH	107-84030	12V	OJ-SH-112LMH	j
	A	1461247-6	OJ-SH-105LMH	107-79010	5V	OJ-SH-105LMH	i
(E)	B	1461247-5	OJ-SH-112LMH	107-79010	12V	OJ-SH-112LMH	h
	A	1461247-3	OJ-SH-124LMH	107-79010	24V	OJ-SH-124LMH	g
	A	1419129-1	OJ-SH-118LMH	107-79010	18V	OJ-SH-118LMH	f
	A	9-1419128-8	OJ-SH-112LMH	107-79010	12V	OJ-SH-112LMH	e
	A	1461247-2	OJ-SH-109LMH	107-79010	9V	OJ-SH-109LMH	d
	A	1461247-1	OJ-SH-106LMH	107-79010	6V	OJ-SH-106LMH	c
	A	8-1419128-1	OJ-SH-105LMH	107-79010	5V	OJ-SH-105LMH	b
	A	1461247-4	OJ-SH-103LMH	107-79010	3V	OJ-SH-103LMH	a
FIG	PART NO	DESCRIPTION	PACKAGE SPEC.	PART B	PART A	TYPE	

RELAY TYPE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±
MATERIAL	FINISH
-	-

DWN	H.Sasaki	-
CHK	Y.Oikawa	-
APVD	A.Nagai	-
PRODUCT SPEC	-	
APPLICATION SPEC	-	
WEIGHT	-	
CUSTOMER DRAWING	-	
SIZE	A3	00779
CAGE CODE	-	
DRAWING NO	1461247	
RESTRICTED TO	-	
SCALE	5:1	
SHEET	2 of 2	
REV	E1	

		UV RESIN	SEAL (VENT HOLE)	16
		EPOXY RESIN	SEAL (BASE & BOBBIN)	15
		JUEW	MAGNETIC WIRE	14
94V-0		P.B.T	CASE	13
94V-0		P.B.T	BASE	12
94V-0		P.B.T	BOBBIN	11
	SOLDER DIP	C.P WIRE	COIL TERMINAL	10
94V-0		P.P.S	CARD	9
		Ag ALLOY	MOVABLE CONTACT	8
		Ag ALLOY	NO.CONTACT	7
		STEEL	HINGE SPRING	6
	SOLDER DIP	Cu ALLOY	NO.TERMINAL	5
	SOLDER DIP	Cu ALLOY	MOVABLE SPRING	4
	NIP	STEEL	CORE	3
	NIP	STEEL	ARMATURE	2
	NIP	STEEL	YOKE	1
INCOMBUSTIBILITY	TREATMENT	MATERIAL	DESCRIPTION	ITEM